




3M-Matic™ Adjustable Case Sealers 200a and 200a3

*Durability for
basic case sealing
at up to 30/minute*



Box capacities –
Length: 6" to no limit
Width: 6" to 21.5"
7" min. for
200a3
Height: 4.75" to 24.5"
Weight: 5 to 85 lbs.

Choice of 2" and 3"
3M™ AccuGlide™ Taping Head 2+

Dual masts with twin lead screws for greater stability of taping head
Emergency stop positioned for quick and easy access

Compression rollers to close flaps before taping

Side guides adjustable to center cases of various widths for the full length of the unit

Bottom belt drive

Rugged construction with 16-gauge welded steel frame and epoxy paint finish

Laced belts with traction grip for reliable feeding and easy replacement

Productivity and performance – bringing it all together in two sturdy, space-saving units for 2" or 3" tape application:

- Gear motor drive for heavy duty shift-after-shift dependability with cases up to 85 pounds
- Consistent top and bottom sealing of RSCs with quick, easy adjustments for a wide range of case heights and widths
- 3M™ AccuGlide™ Taping Head 2+ for low impact sealing that protects cases

Options shown:
Low tape indicator light staff
Infeed and exit conveyors
Locking casters

Specifications

3M™ 3M-Matic™ Case Sealer 200a




2" Scotch® Box Sealing Tapes

3M™ 3M-Matic™ Case Sealer 200a3



3" Scotch® Box Sealing Tapes

200a and 200a3 Footprint



Machine	Tape Size Inches (mm)	Machine Weight Lbs. (kg)	Machine Dimensions Inches (mm)							Electrical	Operating Rate	Drive Belt Speed
			W	L	H	A*	B	C***	F			
					Min		Min					
					Max		Max					
					Masts up		Masts up**					
200a	1.5-2 (36-48)	272 (123.4)	31 (787)	36.5 (927)	53 (1346) 86 (2184) 90 (2290)	18 (457)	24 (610) 35 (889)	4 (102)	24.5 (622)	115V 60Hz 1.9A 220 watts 8' cord	Up to 30 per minute depending on box length	75 fpm (.38 m/s)
200a3	2-3 (48-72)	274 (127.8)										

* Optional infeed/exit conveyors

** 20.5 (520) min, 31 (787) max

*** Optional casters

Use with clean dry boxes in dry, relatively clean environments at 40°F to 120°F (4.4°C to 48.9°C).

Machine	Box Capacities Inches (mm)				Weight Range Lbs. (kg)
	Length Min Max	Width Min Max	Height Min Max	Height Range w/ Masts Raised	
200a	6 (150) Unlimited	6 (150) 21.5 (123.4)	4.75 (120)* 24.5 (625)	6.5 (165) 28.5 (725)	5 (3) 85 (38)
200a3	6 (150) Unlimited	7 (175) 21.5 (123.4)	4.75 (120) 24.5 (625)	6.5 (165) 28.5 (725)	5 (3) 85 (38)

Note: The 3M-Matic™ Adjustable Case Sealer 200a/a3 can accommodate most boxes within the size range listed here.

However, if:

Box Length in Direction of Seal
 Box Height
 is less than .75

Boxes should be test run to ensure proper machine performance.



Contact your 3M representative for special modifications that may be available for sizes not listed.

* 3.75" (90mm) with taping heads adjusted to apply 2" (50mm) tape leg lengths and mast stops relocated.

Note: This technical information and data should be considered representative or typical only and should not be used for specification purposes.

Warranty: Please remember that many factors can affect the use and performance of 3M-Matic™ case sealing equipment in a particular application. User is responsible for determining whether the equipment is suitable for user's method of application and fit for user's particular purpose. 3M warrants that its case sealers and taping heads meet the applicable 3M specifications for the products at the time of shipment. Individual types of equipment and taping heads may have additional warranties as stated on applicable product packages, package inserts, or equipment manuals. THE WARRANTY STATED ABOVE IS MADE IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE AND ANY IMPLIED WARRANTY ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE.

Limitations of Remedies and Liability: If any part of the 3M-Matic™ case sealing equipment is proved to be defective within its specified warranty period. THE EXCLUSIVE REMEDY, AT 3M'S SOLE OPTION, SHALL BE TO REPAIR OR REPLACE THE DEFECTIVE PART. If 3M is unable to repair or replace the part within a reasonable time after receipt thereof, 3M, at its option, will replace the equipment or refund the purchase price. Except where prohibited by law, 3M will not be liable for any loss or damage arising from any 3M product or equipment, whether direct, indirect, special, incidental, or consequential, regardless of the legal theory asserted, including breach of warranty, breach of contract, negligence, or strict liability.



Industrial and Transportation Business Industrial Adhesives and Tapes Division

Bldg. 21-1W-10
 900 Bush Ave.
 St. Paul, MN 55106
 1-800-362-3550
www.3M.com/packaging

3M, 3M-Matic and AccuGlide are trademarks of 3M Company.
 Scotch® is a registered trademark of 3M Company.

Printed in U.S.A.
 © 3M 2007
 70-0707-3332-7