

American-Lincoln®

Encore² High Capacity
Walk-Behind Scrubber



www.americanlincoln.com

The High Capacity Encore² Walk-Behind Scrubber for those Big Jobs

Maximize your cleaning productivity with the Encore² walk-behind scrubber's wide scrub path, oversized tanks and extended run time options. The Encore² is built to withstand the everyday punishment of scrubbing grease and grime in manufacturing plants, car dealerships, beverage distributors and warehouses.

Durable features designed to last include:

- Floating scrub deck and gimble-mounted scrub brushes follow the contours of the floor
- Accu-Track™ breakaway squeegee provides superior water pick up even in tight turns
- Rugged transaxle holds up in the toughest environments
- "Smart" onboard charger protects batteries during charging
- Extra-rugged, one-piece unitized steel chassis

Productivity features include:

- 28 inch, 33 inch, or 38 inch scrub path for extra productivity
- Extra-large solution and recovery tanks to keep your operator scrubbing longer
- No tools required to change the scrub brushes or adjust the squeegee
- Variable scrub head pressure (up to 220 lbs.) cleans in the grimmest conditions



A low brush deck height is extended to allow close edge cleaning, reducing costly secondary operations.




Beyond ergonomics, the Encore² D model also features one-touch scrub control with a multi-function display, auto squeegee lift in reverse and automatic head pressure regulation.

Encore²

American-Lincoln[®]

Walk-Behind Scrubber



KEY FEATURES:

- Long Run Time Capacity
- Adjustable Brush Pressure
- Onboard Battery Charger
- Ergonomic Controls
- Transaxle Drive
- Trim Design for Best Sightline
- Extensive Warranty Coverage

SPECIFICATIONS

Model	S28	S33	S38	D28	D33	D38
Product Code	05241A 05242A	05262A 05261A	05281A	05252A 05251A	05272A 05271A	05291A
Cleaning Swath	28 inches	33 inches	38 inches	28 inches	33 inches	38 inches
Power Supply	36 volt (6 - 6 volt batteries) 250 or 330 AH					
Vacuum Motor	1 HP three stage					
Solution Tank	30 gallons					
Recovery Tank	30 gallons					
Brush Motors (2)	1 HP					
Brush Speed	200 RPM					
Brush Pressure	150 to 220 lbs					
Auto Brush Pressure Control	No			Yes		
Auto Squeegee Lift in Reverse	No			Yes		
Speed, Forward	Variable to 230 ft/min					
Speed, Reverse	Variable to 180 ft/min					
Cleaning Grade	6 degree incline					
Charger, On-board	36V, 21A, 115V/60Hz					
Length of Machine	67.3 inches					
Width of Machine	30 inches	36 inches	40 inches	30 inches	36 inches	40 inches
Height of Machine	43.75					
Shipping Weight with 330 AH Batteries	1308 lbs	1318 lbs	1328 lbs	1308 lbs	1318 lbs	1328 lbs
Warranty	Polydur [®] Tanks-8 Years, Parts-3 years, Labor-1 year, Batteries-90 days full, 18 mos. pro-rated (American-Lincoln battery warranty doubles with purchase of CBMS).					

WHO USES THIS MACHINE:

- Manufacturing plants
- General warehouses
- Car dealers
- Automotive plants
- Beverage distributors

WHAT DOES IT DO BEST:

- Fast routine scrubbing
- Deep scrubbing
- Double scrubbing

WHAT ENHANCES ITS PRODUCTIVITY:

- Large solution and recovery tanks
- Long run time battery capacity
- Accu-Track™ breakaway squeegee features no tool adjustment
- Highly maneuverable with excellent sightline
- In neutral, solution and brushes turn off
- Easy to operate
- Automatic head pressure regulation (D Models)
- Automatic squeegee lift in reverse (D Models)
- Drain and fill from the rear of the machine
- Leaves the floor dry to reduce slip/fall hazards

WHAT ARE THE SAFETY FEATURES?

- Dynamic braking slows machine to a smooth stop
- Safety yellow palm start buttons
- Key switch to prevent unauthorized use
- Circuit breakers protect all electrical components
- Automatic parking brake option

American-Lincoln

1100 Haskins Rd
Bowling Green, OH 43402
www.americanlincoln.com

DISTRIBUTED BY:

Customer Service: 1-800-331-7692
Fax Orders to: 1-877-877-2586
Technical Service: 1-800-331-7691

©2005 Nilfisk-Advance, Inc., Printed in U.S.A., All Rights Reserved. Specifications subject to change without notice. Form L1665L 1-05

