

OVEN LOADER



- **Designed for Side Feed Loading (left or right side) or Front Feed Loading Depending on Customer Requirements**
- **Easy to Move With Caster and Quick Disconnects**

OVEN LOADER

FEATURES & BENEFITS

- Loading rate up to 6 cycles/minute
- Aluminum finish panels
- Unit includes
 - Load pusher
 - Feed conveyor
 - Discharge conveyor
- Made to fit new AMF Vesta or existing B.P. 970/935 ovens
- Other models available

MECHANICAL FEATURES

- Mounted on heavy duty casters to allow removal from the front of the oven.
- The feed conveyor consists of full table top high temp plastic belt to allow a smooth pan transfer from the loader conveyor to the oven tray during the loading cycle.
- The discharge conveyor consists of full table top high temp plastic belt to allow a smooth pan transfer from the loader conveyor to the oven tray during the loading cycle.
- Lift out panels are installed where frequent maintenance is required.

ELECTRICAL FEATURES

Standard loader set-up includes the following:

- Control panel
- Variable speed drive for the load conveyor
- All field devices (P.E. limit switches)
- Optical cam box or optional PLC control for pusher
- Quick connect plug and junction box for the oven interlock
- Two push-button stations if needed (loader can be set up to be controlled by an existing oven control panel)

Headquarters:
2115 W. Laburnum Ave.
Richmond, Virginia 23227
Tel: 1-800-225-3771
or 1-804-355-7961
Fax: 1-804-342-9724
sales@amfbakery.com

Europe Office:
6 The Sidings
Station Road, Guiseley
Leeds LS20 8BX, England
Tel: 44-1943-875703
Fax: 44-1943-871806
sales-europe@amfbakery.com

Asia Office:
Room 15-2, A-Building
Thunis Dev. Building
No.11 Hui Xin East St.
Chaoyang District
Beijing, China 100029
Tel: 86-10-64823613
Fax: 86-10-64934259
sales-asia@amfbakery.com

FOR MORE INFORMATION PLEASE CALL YOUR ACCOUNT MANAGER OR

1-800-BAKERS-1
www.amfbakery.com