

Belshaw Adamatic

## BX Convection Oven, 4-Tray

Models: BX4-C, BX4-S

### Features

- Produces an even bake
- Steam injection standard on all ovens
- 2 programmable controller options
  - Classic (9 programs) - BX4-C
  - Smartbake (99 programs) - BX4-S
- Compatible with 26" x 18" trays
- BX4 ovens are stackable
- 'Cool to Touch' oven-doors
- ETL certified to UL-197 and NSF-4

### Options

- Smartbake controller (for this option choose BX4-S model)
- Other pan spacing and capacities are available (consult factory)
- Stand for single BX4 oven (8 shelves)
- Stand for double stacked BX4 ovens (5 shelves)
- 8 shelf proofer base



Model: BX4-C (9-program Classic controller)



Model BX4-S (99-program graphical Smartbake controller)



BX-4 on single oven stand



Two BX-4 ovens on stacked oven stand



**Classic Controller (BX4-C)**

Up to 9 programs. For each program, you control:

- Bake time
- Bake temperature
- Steam duration
- Damper open/shut
- Settings can be changed while the program is running.
- Programs are set on control panel (no download from computer).

**SmartBake Controller (BX4-S)**

Holds up to 99 programs. Six phases possible in each program. For each phase, you control:

- Bake time
- Bake temperature
- Steam duration
- Fan cycles. Fan can reverse direction up to 9 times per bake program.
- Damper open/shut.
- Programs are set on control panel or via download from computer.
- The controller includes prominent countdown timer with audible signal at end of program.

Classic Controller



Standard interface

Smartbake Controller



Monitoring progress of bake

Easy-to-use screens

Fast menu choices

Model	BX4
<b>Operation</b>	
Shelves	4
Pan size	18" x 26"
Shelf spacing	3.5"
<b>Dimensions</b>	
Overall Width	34"
Overall Depth	46" (inc. 2" handle)
Overall Depth (w/Door open)	68"
Overall Height (oven only)	20.75"
Overall Height (oven and stand)	67.5"
Clearance requirement	2" at rear only
Net weight (1 oven)	370 lbs
Net weight (Short stand)	145 lbs
Net weight (Tall stand)	206 lbs
Net weight (Proofer)	311 lbs
Shipping Class	85
<b>Electrical</b>	
Power (2 connections)	<ul style="list-style-type: none"> <li>• 208-220V/60/3 @ 20.8 to 22.3A</li> <li>• 120V/60/1 @ 7.8A</li> </ul>
Connectors	<ul style="list-style-type: none"> <li>• NEMA L15-30 (3+G) 6 Ft</li> <li>• NEMA 5-15</li> </ul>
<b>Water supply</b>	
	30psi minimum
<b>Damper</b>	
	Butterfly type

