

# BANDSAW 1750

Professional range

Round Capacity: 5.9" @ 90°  
3.9" @ 45°  
Square Capacity: 6.3" x 5.5" @ 90°  
4.7" x 3.9" @ 45°



INNOVATIVE CLUTCHED  
BAND TENSIONING SYSTEM

Technical Features:

- Cuts without lubrication
- Easy to carry
- Adjustable bar stop-rod for mass-produced cuts (L=19.6")
- Blade tensioning device with clutch to adjust the proper blade tension
- Reverse blade rotation provides 40% faster cutting
- Adjustable left cutting to 45° with single phase motor
- Quick blade change with no tools necessary
- Base with integrated quick sliding vice

FASTER  
40%

"NG SYSTEM":  
OPPOSITE BLADE  
ROTATION DIRECTION

POWERFUL  
2000 W MOTOR  
EQUIPPED  
WITH ELECTRONIC  
DIGITAL SPEED REGULATOR  
"CONSTANT SPEED"

Art. **PATENTED**

# NG160

INTEGRATED QUICK  
SLIDING VICE

EXTRAORDINARY CUTTING  
CAPACITY: 160 X 140 mm



HEM Inc., whose policy is one of continuous improvement, reserves the right to change the design, price, and/or specifications at any time, without notice, and without incurring any obligations.

**femi**  
Muda' He Wastage

Packaging - Processing  
**Bid on Equipment**  
1-847-683-7720

[www.bid-on-equipment.com](http://www.bid-on-equipment.com)