

BANDSAW 2700

Industrial range

Round Capacity:

9" @ 90°

7" @ 45°

4.5" @ 60°

Square Capacity:

11" x 6.7" @ 90°

6.7" x 6.7" @ 45°

4.3" x 3.15" @ 60°

Packaging - Processing

Bid on Equipment


1-847-683-7720

www.bid-on-equipment.com



new!

ALSO AVAILABLE AS NG280MX WITH SLIDING VISE & 60° LEFT AND 45° RIGHT MITERING



"NG SYSTEM":
OPPOSITE BLADE
ROTATION DIRECTION

FASTER
40%

24 VOLT
CONTROL PANEL

Art. **PATENTED**

NG280_M

MANUAL

WHEELS MOUNTED
ON FLANGES WITH
DOUBLE TAPERED BEARING

LARGE CUTTING
CAPACITY: 280 MM

DOUBLE BLADE GUIDE
WITH ADJUSTABLE
WIDIA RUNNERS
AND BEARINGS

Technical Features:

- Adjustable bar stop-rod for mass-produced cuts (L=23.62")
- Blade tensioning device with light indicator & safety microswitch for proper blade tensioning
- Miter cutting to 60° left, quick locking device at 45° & 60°
- Quick blade change with no tools necessary
- Reverse blade rotation provides 40% faster cutting
- 3 phase, 2 speed motor
- Adjustable flex-tube for coolant
- Arm mounted on double tapered bearing to eliminate clearances

HEM Inc., whose policy is one of continuous improvement, reserves the right to change the design, price, and/or specifications at any time, without notice, and without incurring any obligations.

