



Technical data SFXmagnus

filter type	screen area		heating capacity in watt		heater zones		pressure in bar max. ⁽¹⁾	temp. in °C max. ⁽²⁾	Q in kg/h ⁽³⁾	dimensions in mm								weight in kg
	active in cm ²	total in cm ²	electric	oil / vapor	electric	oil / vapor				A	B	C	D	E	F	G	H ⁽⁴⁾	
SFXmagnus 45	90	250	7500	8500	3	2	350	320	400	800	300	720	700	190	110	185	20	250
SFXmagnus 60	160	450	8000	10000	3	2	350	320	700	830	360	750	800	220	125	185	20	350
SFXmagnus 75	220	600	8500	10000	3	2	350	320	900	880	390	800	900	230	140	232	25	450
SFXmagnus 90	350	1000	19000	22000	4	2	300	320	1000	1100	500	1050	960	280	160	328	30	800
SFXmagnus 130	500	1400	19000	25000	4	2	300	320	2000	1150	530	1100	1000	300	175	362	30	950
SFXmagnus 150	600	1600	19000	25000	4	2	300	320	2500	1200	550	1200	1050	320	175	405	35	1050
SFXmagnus 175	1000	2200	25000	32000	4	2	250	320	3500	1300	650	1300	1100	380	250	405	40	1700
SFXmagnus 200	1300	3100	35000	36000	6	2	200	320	5000	1300	750	1350	1400	450	270	555	45	3500
SFXmagnus 250	1700	4000	46000	48000	6	2	200	320	7800	1400	800	1400	1500	500	320	605	50	4200
SFXmagnus 330	2900	6400	-	60000	-	2	200	320	12000	1700	950	1700	1550	550	350	695	55	7000
SFXmagnus 400	3800	8700	-	60000	-	2	200	320	16000	1800	1100	1800	1600	650	400	800	60	9000
SFXmagnus-D 330	5800	12800	-	60000	-	3	200	320	24000	1800	950	1700	1600	550	350	1100	55	9500
SFXmagnus-D 400	7600	17400	-	80000	-	3	200	320	32000	1900	1100	1800	1700	650	400	1400	60	14000

(1) = High pressure versions available as an option.

(2) = Up to 400 °C possible as an option.

(3) = Based on: 1000 Pas, 60 µm und Δp 40 bar.

(4) = The dimension „H” can be freely chosen, the values given are minimum values.