



Wide Flange WF130HA-DC-C

Capacity: 18" High x 27" Wide
Blade Size: 1-1/2" x 21'0" x .050"
Arm Tilt: 9.2°
Motor: 10 HP
Hydraulics: 2 HP



**Shown w/ Optional Full Capacity Top Clamps*

Standard Features:

- Swing-Away Console - All Function Control
- Full Stroking Bi-Directional Vises
- 0-72" Stroke Bar-Feed
- w/ Rollers All the Way Through
- Computer Controlled Feed System
- Material Jog
- Chip Conveyor System
- Cut Watcher System
- Inverter Blade Drive
- LED Blade Speed Readout
- Powered Blade Tansion
- Powered Guide Arm
- Electronically Controlled Traverse (ECT)
- Controls Feed Rate & Cutting Force
- 24" Roller Discharge Table
- Flood Coolant System



Optional Features:

- Guide Cap Camlocks
- Bi-Directional Outboard Powered Vise
- Bi-Directional 3rd Vise on Feed
- Set of Full Capacity Top Clamp
- Main & Feed Vise
- Full Capacity Top Clamp - Outboard Vise
- Laser Light System
- Shadow Light System
- Cutting Vibration Dampening System
- Hydraulic Computer Controlled Traverse
- Spray Mist Lubrication System
- Pedestal Mounted Console

www.hemsaw.com

P. O. Box 1148 • Pryor, OK • 74362
Toll Free: (888) 729-7787 • Phone: (918) 825-4821
Fax: (918) 825-4824 • E-Mail: info@hemsaw.com

Hem, Inc., whose policy is one of continuous improvement, reserves the right to change the price, specifications, or design, as well as discontinue at notice and without incurring any obligations. Dimensions may vary. Please contact Hem, Inc. for a certified dimensional drawing of your specific model. All rights reserved.

Packaging - Processing
Bid on Equipment
1-847-683-7720
www.bid-on-equipment.com