



Wide Flange WF160LA-DC-C

Capacity: 25" High x 30" Wide

Blade Size: 2" x 26'9" x .063"

Arm Tilt: 9.2°

Motor: 15 HP

Hydraulics: 5 HP



**Shown w/ Optional Full Capacity Main, Feed & Outboard Vise Top Clamps*

Standard Features:

- Swing-Away Console - All Function Control
- Full Stroking Bi-Directional Vises
- 0-72" Stroke Bar-Feed w/ Drop-In Rollers
- Computer Controlled Feed System
- 3rd Vise on Feed
- Material Jog
- Guide Cap Camlocks
- Chip Conveyor System
- Cut Watcher System
- Variable Frequency Controller
- LED Blade Speed Readout
- Powered Blade Tansion
- Powered Guide Arm
- Electronically Controlled Traverse (ECT)
 - Controls Feed Rate & Cutting Force
- 24" Roller Discharge Table
- Flood Coolant System

DESIGNED AND BUILT IN THE



Optional Features:

- Bi-Directional Outboard Powered Vise
- Full Capacity Top Clamp - Main Vise
- Set of Full Capacity Top Clamp
 - Main & Feed Vise
- Full Capacity Top Clamp - Outboard Vise
- Laser Light System
- Shadow Light System
- Cutting Vibration Dampening System
- Hydraulic Computer Controlled Traverse
- Spray Mist Lubrication System
- 2-5/8" Blade Option
- Pedestal Mounted Console

www.hemsaw.com

P. O. Box 1148 • Pryor, OK • 74362

Toll Free: (888) 729-7787 • Phone: (918) 825-4821

Fax: (918) 825-4824 • E-Mail: info@hemsaw.com

Hem, Inc., whose policy is one of continuous improvement, reserves the right to change the price, specifications, or design, as well as discontinue at notice and without incurring any obligations. Dimensions may vary. Please contact Hem, Inc. for a certified dimensional drawing of your specific model. All rights reserved.

Packaging - Processing
Bid on Equipment
1-847-683-7720
www.bid-on-equipment.com