



# Wide Flange WF190LM-DC

**Capacity:** 25" High x 44" Wide

**Blade Size:** 2" x 29'0" x .063"

**Arm Tilt:** 9.2°

**Motor:** 15 HP

**Hydraulics:** 5 HP

DESIGNED AND BUILT IN THE  
U.S.A. 



*\*Shown w/ Optional Full Capacity Top Clamps*

Standard Features:

- Swing-Away Console - Manual Control
- Full Stroking Vise
- Bi-Directional Main Vise
- Guide Cap Camlocks
- Variable Frequency Controller
- LED Blade Speed Readout
- Powered Blade Tansion
- Powered Guide Arm
- Electronically Controlled Traverse (ECT)
  - Controls Feed Rate & Cutting Force
- 24" Roller Discharge Table
- Flood Coolant System

Optional Features:

- Chip Conveyor System
- Bi-Directional Outboard Powered Vise
- Full Capacity Top Clamp - Main Vise
- Full Capacity Top Clamp - Outboard Vise
- Cut Watcher System
- Laser Light System
- Shadow Light System
- Cutting Vibration Dampening System
- Hydraulic Computer Controlled Traverse
- Spray Mist Lubrication System
- 2-5/8" Blade Option
- Pedestal Mounted Console

[www.hemsaw.com](http://www.hemsaw.com)

P. O. Box 1148 • Pryor, OK • 74362

Toll Free: (888) 729-7787 • Phone: (918) 825-4821

Fax: (918) 825-4824 • E-Mail: [info@hemsaw.com](mailto:info@hemsaw.com)

Hem, Inc., whose policy is one of continuous improvement, reserves the right to change the price, specifications, or design, as well as discontinue at notice and without incurring any obligations. Dimensions may vary. Please contact Hem, Inc. for a certified dimensional drawing of your specific model. All rights reserved.

**Packaging - Processing**  
**Bid on Equipment**  
1-847-683-7720  
[www.bid-on-equipment.com](http://www.bid-on-equipment.com)