



Wide Flange WF190MRB-DC

- Capacity:** 25" H x 44" W @ 90°
25" H x 27" W @ 45° Both Directions
- Blade Size:** 2" x 30'6" x .063"
- Arm Tilt:** 7°
- Motor:** 15 HP
- Hydraulics:** 5 HP



Rotary Bearing Base



Standard Features:

- Free Standing Control Console w/ 25' Umbilical
- Powered Blade Tension
- Powered Moveable Guide Arm
- Power Miter w/ Angle Readout
- LED Blade Speed Readout on Console
- Variable Frequency Controller for Blade Speed
- Vising on Both Sides of Blade
- Flood Coolant System
- Roller Base Machine
- Blade Chip Brush
- Blade Stall Switch
- Flat Carbide Blade Guides
- Guide Cap Camlocks
- Hydraulic Computer Controlled Traverse (HCCT)
- Adjustable Clamping Pressure (0-2, 500 lbs)
- Adjustable Feed Rate & Cutting Pressure
- Blade Guards for Safety



Optional Features:

- Chip Auger System
- Cut Watcher System
- Cutting Vibration Dampening System
- Laser Light System
- Shadow Light System
- Spray Mist Lubrication System
- Top Clamp Vising - Input Side
- Top Clamp Vising - Output Side
- 4' Telescoping Table - Input Side
- 4' Telescoping Table - Output Side

www.hemsaw.com

P. O. Box 1148 • Pryor, OK • 74362

Toll Free: (888) 729-7787 • Phone: (918) 825-4821

Fax: (918) 825-4824 • E-Mail: info@hemsaw.com

Hem, Inc., whose policy is one of continuous improvement, reserves the right to change the price, specifications, or design, as well as discontinue at notice and without incurring any obligations. Dimensions may vary. Please contact Hem, Inc. for a certified dimensional drawing of your specific model. All rights reserved.

Packaging - Processing
Bid on Equipment
1-847-683-7720
www.bid-on-equipment.com