

KR435 Mini Tabber

Kirk-Rudy's most affordable tabbing system

Priced thousands less than comparable systems, the KR435 utilizes many of the same features that made the KR535 a best seller.

Key features like side register belts, side to side table top adjustment and automatic tab sensor setup keeps the tabbing process consistent and reliable. Also, the KR435's operator interface utilizes all the same user-friendly programs found on the KR 535 that simplify operator training and setup.

The KR435 handles large 16" diameter rolls and runs all major types of tabs as well as pressure sensitive stamps and labels of various shapes and sizes. Multiple tabs or labels can be applied in a single pass. The KR435 is setup to Tab left-side only but can be ordered to Tab right-side. The KR435 runs in line with most standard addressing systems.

**Industrial
Tabbing
Technology
at
Affordable
Costs!**



** Guards may have been removed for clarity; do not operate machine without guards in place.



KR435 Mini Tabber

Kirk-Rudy's most
affordable tabbing system

**General Specifications

| Physical | English | Metric |
|-----------------|---------|----------|
| Length | 36" | 91.4 cm |
| Width | 26" | 66.0 cm |
| Tabletop Height | 33.25" | 84.5 cm |
| Overall Height | 70" | 177.8 cm |

Electrical Requirements

| Voltage | Amp | Hz |
|-------------|------|-------|
| 120/220 VAC | 10/5 | 50-60 |

Maximum Operating Speeds

| | |
|----------------|----------------------|
| Single tabbing | 25,000 pieces / hour |
| Double tabbing | 25,000 pieces / hour |

Note: Speeds are dependent on material being fed.

Products

| | | |
|--------------|---|--|
| Tabs | Min 0.50" dia. (1.3 cm) | Max 2" dia. (5.1 cm) |
| Tab Quantity | 1 to 6 Tabs or Stamps | |
| Labels | 3" (7.6 cm) W x 2" (5.1 cm) L standard larger sizes optional | |
| Materials | Minimum: 3.50" x 5.00" (8.9 cm x 12.7 cm) (single sheet) | Maximum: 13" W x 14" L x .62" (33 cm x 35.6 cm x 1.6 cm) (labeling only) 11" W x 14" L x .18" (29 cm x 35.6 cm x .5 cm) (both) |

Features & Benefits:

- Side register belts for tight tabs
- Quick setup
- Automatic tab sensor calibration
- Automatic tab location feature
- Side to side tabletop adjustment
- Industry standard motors and control
- Quick-release top belt control.
- Runs in-line with most addressing systems

Options:

- Single crank hydra lift kit for height adjustment up to 5 inches.
- KR 496F Friction feeder and KR415 Interface conveyor.
- Wide label kits.
- KR 565 Label Splicing Unit
- KR 730 Roller Registration Conveyor



** Specifications subject to change without notice.