

LITTLE DAVID®



Uniform Case Sealer

The Little David® Uniform LD-7 is an economical top and bottom case taper designed to reliably seal large runs of uniform cases. The LD-7 uses pressure sensitive tape and incorporates self-centering side rails, as well as a heavy-duty 2" x 4" mast.



These are what make a reliable case sealer:

- Low Maintenance
- UL Listed
- Quick Changeover
- Safe Single Mast
- Economical
- Simple Hand Tighten Adjustments
- Interchangeable Tape Cartridges

(Photo shows optional infeed table.)

Packaging – Processing

Bid on Equipment

1-847-683-7720

www.bid-on-equipment.com

LD-7

Safe —

- Single mast design allows clear access to all components


Optional Little David MicroJet® adapter allows you to code while you seal.



57-35/64" (146.2cm)

31-5/64" (78.9cm)

35-49/64" (90.8cm)



Top cartridge tips back on head for tape threading.

Flexible —

- Interchangeable CaseLocker® ST top and bottom tape cartridge.

Quick Change Over —

- Extended side rails center box
- Convenient palm grip knobs allow for easy slide and lock adjustments

Leg extensions allow for easy height adjustments from 22-1/4" to 30-1/4".

Features:

Reliable Performance — Warranty

- 1 Year all components*
- 2 Years Gear Reducer
- 3 Years Cartridge*

*Moving and wear parts are not included. Other restrictions may apply. Consult Loveshaw or your authorized Little David® Distributor for details

Easy Operation —

- Plug in operation
- Minimal operator training required
- Sealed drive system
- CaseLocker™ ST tape cartridge requires no lubrication

Specifications:

Power Requirements:

115 – 220 volts, single phase, 60 cycle
(other voltage available, consult Loveshaw)

Operating Speed:

Continuous belt drive; 80'/minute (24.4 m/min.)
(production rate depends on box size & operator dexterity)

Weight:

196.5 lbs (89 kg) uncrated

Closure Material:

Pressure sensitive tape
Width: 1-1/2" (38 mm) to 2" (51 mm)
Roll Size: up to 15" (381 mm) diameter

Case Capacity: (with 2" wide Caselocker® ST Cartridge)

Min: Height 4-1/2" (114 mm), Width 4-1/2" (114 mm), Length 4-1/2" (114 mm)

Max: Height 24" (610 mm)*, Width 22" (559 mm), Length infinite

Note: Certain length x width x height combinations may not process due to unstable conveying conditions.

Flexible —

- Tapes boxes from 4-1/2" (114 mm) to 24" (610 mm)
- Compact design allows for portability

Safe —

- UL listed
- Single mast design allows clear access
- Knife guard system of the CaseLocker™ ST tape cartridge allows the blade to be exposed only when rollers are depressed

Options:

- Casters
- Available for 3" wide tape
- Leg adjustments to accommodate various conveyor heights
- High mast for box heights to 34" (864 mm)
- Front and rear solid or roller pack table
- Squeezers

LOVESHAW **LOVESHAW Europe**
an **ITW** Company A Division of ITW Ltd.

LITTLE DAVID PRODUCTS DIVISION
Route 296 Box 83
South Canaan, PA 18459
(570) 937-4921 Fax (570) 937-3229
1(800) 572-3434

Unit 9 Brunel Gate,
West Portway Industrial Estate
Andover, Hampshire England SP 10 3 SL
Tel: (1264) 357511 Fax: (1264) 355964

visit
www.loveshaw.com



Packaging - Processing
Bid on Equipment

1-847-683-7720

www.bid-on-equipment.com