



Accubar™ Bar Code Verifier

*Reliable bar code scanner
validates symbol accuracy
directly on the production
line, enhancing efficiency
and quality control.*



The Nordson Accubar bar code verifier monitors and validates symbol accuracy in high-speed packaging and converting operations. Unacceptable codes can trigger an alarm, machine stop, ejector or marker. Your product quality is protected against faulty codes and mixed lots that can increase operating costs.

The microprocessor-based control provides efficient scanning using advanced laser technology. Capable of operating at line speeds up to 425 meters per minute (1400 ft/min), the Accubar verifier accommodates high-output production of folding carton manufacturing, case sealing, container filling, and die cutting.

Further efficiency is provided with pre-programmed bar code formats, adding product changeover flexibility without complicated format programming. The control's comprehensive decoding feature recognizes diverse formats. These include black, colored and fine code lines; truncated codes; and ladder or picket-fence scanning.

Programming a specific code to memory is easy. Operators simply align the bar-coded product to the photocell, focus the laser on the bar code and press the memory button. The symbol in memory becomes the decode default that the scanner verifies.

When combined with the Nordson G-NET verification system, you can increase productivity through automatic tracking and ejection. The G-NET system also accepts additional glue detectors, cellophane detectors and other end-product inspection sensors.

Efficient scanning technology enhances on-line quality management.

■ **Microprocessor-based control** accurately scans and verifies bar codes at line speeds up to 425 meters per minute (1400 ft/min).

- **Diverse format decoding** accepts black, colored, and fine code lines; truncated codes; and ladder or picket-fence scanning.
- **Comprehensive bar code formats** are pre-programmed for quick setup and line start.
- **Instantaneous faulty code detection** triggers an alarm, machine stop, ejector or marker for immediate notification, removal or identification.
- **Compact console and scanner** install easily on parent machines in tight mounting spaces.
- **Convenient RS232 computer interface** allows configuration and monitoring from a remote location.
- **Tracking and ejection capability** consolidates reject removal or marking.

Packaging - Processing

Bid on Equipment

1-847-683-7720

www.bid-on-equipment.com

Specifications

| | |
|------------------------------|---|
| Scanning Parameters | Rotating polygon uni-directional 2000 sweeps/second, picket-fence or ladder operation |
| Decoding Capabilities | Codabar, code 39, interleaved 2 of 5, code 93, code 128, UPC/EAN, pharmacode |
| Light Source | Laser diode |
| Photocell | 12 VDC @ 250 mA open collector input 5-pin 180° DIN connector |
| Relay Contacts | 230 VAC @ 5 A |
| External Link Output | Open drain 500 mA sink, 50 VDC maximum |
| Electrical Service | 115/230 VAC, 50/60 Hz, 0.08 A |
| Temperature Rating | 0° to 60° C (32° to 140° F) |
| Safety Class | Class II |

Dimensions

| Dimension mm (in.) | Scanner | Console |
|--------------------|----------|------------|
| Height | 41 (1.6) | 121 (4.75) |
| Width | 58 (2.3) | 235 (9.25) |
| Depth | 76 (3.0) | 190 (7.5) |



For more information, talk with your Nordson representative or contact your Nordson regional office.

United States
 Duluth, Georgia
 Telephone: (800) 683-2314
 Toll-free Facsimile:
 (866) 667-3329

Canada
 Markham, Ontario
 Telephone: (800) 463-3200
 Facsimile: (905) 475-8821

Europe
 Udenhout, The Netherlands
 Telephone: (31) 13-511-8777
 Facsimile: (31) 13-511-3995

Japan
 Tokyo, Japan
 Telephone: (81) 3-5762-2700
 Facsimile: (81) 3-5762-2701

**Asia/Australia/
 Latin America**
 Amherst, Ohio
 Telephone: (440) 985-4797
 Facsimile: (440) 985-1096

www.nordson.com



When you expect more.®