

PFM Tornado LD



It is a fast horizontal Flow Wrap machine, which produces airtight packages starting from a reel of heat-sealable packaging material. Tornado LD is especially designed for M.A.P.

Speed: the exclusive Long Dwell sealing system allows the machine to achieve 100 hermetically sealed and aesthetically perfect packages per minute.

Easy to clean and sanitize: cantilever concept and stainless AISI 304 construction. The mechanical components are at the back of the machine in separate enclosures while the sealing units and the conveying belts are at the front of the wrapper.



Examples of packagable products

Servo on line version:

a new PFM User Friendly and intuitive programming system, which uses a touch screen panel for easily setting the machine functions.

The format change is performed automatically, in particular with regards to:

- Bag length setting.
- Dwell setting.
- Product phasing.
- Print centering setting.
- Date coder printing position setting.

It also features special functions such as the "no product no bag" option and the automatic adjustment of the crossways sealing unit height. Possibility of on-line remote support system.



Main standard features:

- 2 mt. long infeed conveyor with interchangeable pushers or flat belt.
- Forming box for packaging material with height and width adjustment for easier format change.
- Double self-centering reel holders with built-in brake.
- Print registration system.
- "Cantilevered" type construction.



Examples of packagable products



Available models:

- Version with top film reel.
- Version with bottom film reel.
- Electronic Version.
- Servo Version.
- LVA Servo: automatic adjustment of the bag length according to product length.
- Servo Remote - Assistance Service.

Packaging - Processing
Bid on Equipment

1-847-683-7720

www.bid-on-equipment.com