

Series PT-300HT (30 Cu. Yd) Hydraulic Tailgate Self-Contained Compactor



The PT-300HT Compactor has been engineered to provide many years of reliable service. The Compactor is constructed with Hydraulic Cylinders to allow the unit to be emptied through the same opening that material was compacted into eliminating the need for additional space and eliminating "Costly Turn-Around Time".

Specifications

Charge Box Capacity2.0 Cu Yd
Clear Top Opening41" x 58"

Performance Characteristics

Cycle Time31 sec
Total Normal Force43,000 lbs
Total Maximum Force51,600 lbs
Normal Ram Face Pressure23.8 psi
Maximum Ram Face Pressure28.8 psi

Electrical Equipment

Electrical Motor3 Phase 208/ 230/ 460 10 hp
Electrical Control Voltage120 VAC
Total U.L Approved	
Standard 3 Button Controls:	On/Off Key Switch, Mushroom Stop, Auto/ Reverse
Connected to 13' Sealtite	

Hydraulic Equipment

Hydraulic Pump Capacity10.5 gpm
Normal Pressure2000 psi
Maximum Pressure2400 psi
Hydraulic Cylinder (2)4" Bore 2.5 " Rod



ENVIRONMENTAL INDUSTRY
ASSOCIATION



INTERNATIONAL SOCIETY OF SAFETY ENGINEERS
THE WORLD OF THE PROFESSIONAL SAFETY ENGINEER

