



800-523-3654

BALER & COMPACTOR

www.ptrco.com

Stationary Compactors



TP-2500HD

Tram-Pak Stationary Compactor

Designed For

- * Retailers * Hospitals * Hotels * Distribution Centers *
- * Manufacturing Centers * Recycling Centers * Home Centers *

Our TP-2000SP (Short Profile) compactor was our response to customers battling space constrictions and those who could not accommodate a long chute. We managed to construct a twin cylinder machine with high compaction forces and an overall length of 78 inches. All components are built using heavy-duty structural steel components and welded by AWS certified technicians. This unit has total U.L. approval, standard 3 button controls (On/Off key switch, mushroom stop, auto reverse) and a 13' Sealite.

Specifications

Charge Box Capacity	2 Cu Yd
Clear Top Opening (L x W)	40" x 60"
Capacity Per Hour	58.7 cy/hr

Electrical Equipment

Electrical Motor 208 / 230 / 460	3 Phase
Electrical Control Voltage	120 VAC

Performance Characteristics

Cycle Time	31 sec
Total Normal Force	43,000 lbs
Total Maximum Force	51,600 lbs
Normal Ram Face Pressure	23 psi
Maximum Ram Face Pressure	29 psi

Hydraulic Equipment

Hydraulic Pump Capacity	10.5 gpm
Normal Pressure	2000 psi
Maximum Pressure	2400 psi
Hydraulic Cylinder	4" Bore
Hydraulic Cylinder	2.5" Rod
Weight	4,500 lbs



PTR Baler & Compactor Company • 2207 E Ontario St. • Philadelphia, PA 19134
 215-533-5100 • (FAX) 215-533-8906 • 800-523-3654 • www.PTRCO.com

Printed in the U.S.A.
 © PTR Baler & Compactor