



800-523-3654

# BALER & COMPACTOR

www.ptrco.com

## Pre-Crusher Compactors

### TP-4000-PC

### 4 Cu. Yd. Pre-Crusher Compactors

The Pre-Crusher Series was designed to destroy product prior to compacting. This machine has a heavy duty guillotine door that is used by the ram as a wall to compact against before cycling again into the container.

#### Hard to Destroy Materials such as.....

- Steel Drums
- Barrels
- Skids
- Product Destruction



Each unit has total U.L approval, standard 3 button controls (On/Off Key Switch, Mushroom Stop, Auto/Reverse) and connected with a 13' Sealtite.

Specifications	3 cu yd	4 Cu Yd	5 Cu Yd	Electrical Specifications	3 cu yd	4 Cu Yd	5 Cu Yd
(Mfrs Rating)	3 cu yd	4 cu yd	5 cu yd	Electrical Motor	20 HP	20 HP	30 HP
Clear Top Opening	58" x 68"	60" x 68"	85" x 57"	Voltage	3 Phase 208/ 230/ 460 volt		
Capacity Per Hour		162 cy/hr		Electrical Control Voltage	120 VAC		
Performance Characteristics				Hydraulic Specifications			
Cycle Time	65 sec	62 sec	55 sec	Pump Capacity	18 gpm	18 gpm	51 gpm
Total Normal Force	59,346 lbs	59,346 lbs	80,776 lbs	Normal Pressure	2100 psi	2100 psi	2100 psi
Total Maximum Force	67,872 lbs	67,872 lbs	92,316 lbs	Max Pressure	2400 psi	2400 psi	2400 psi
Normal Ram Face Pressure	29 psi	29 psi	40 psi	Hydraulic Cylinder	6"	6"	7"
Maximum Ram Face Pressure	33 psi	33 psi	46 psi	Pre-Crusher Cylinder	3.5"	3.5"	3.5"



PTR Baler & Compactor Company • 2207 E Ontario St. • Philadelphia, PA 19134  
 215-533-5100 • (FAX) 215-533-8906 • 800-523-3654 • www.PTRCO.com



Printed in the U.S.A.  
 © PTR Baler & Compactor