

CAPABILITIES PROFILE

Q33

INDUSTRY

Manufacturing
Distribution

PRODUCTS

Corrugated boxes
Cases
Pallets

APPLICATION

Flat Panel Labeling:
Top Leading Panel
Side Trailing Panel
Bottom Corner Wrap

PRODUCTION RATE*

RFID

Up to 100 PPM Apply
Up to 60 PPM W/Reject

Thermal Transfer

Up to 100 PPM

*Dependent on Label Size

New Q33 Modular Applicator

This NEW Applicator is uniquely suited for the most demanding, variable information labeling requirements.

The Q33 is constructed of anodized aluminum and stainless steel and features a 12" label unwind, linear slide air cylinder, variable torque waste rewind, all quick disconnect electronics and pneumatics.

Low label, low ribbon, end of ribbon and end of media faults are included with a two lamp fault indicator.

When used with an OEM printer, the Q33 provides next-out printed labels with numerous resident fonts while supporting all popular bar code formats.

The high performance chassis utilizes a series of applicator modules including air-tamp, air-blow, tamp-blow, wipe-on and various pneumatic swing arms for side, top, leading edge, adjacent side or corner wrap labeling applications.

The modular design of the Q33 allows the system to be upgraded with future technological developments in RFID.



QUADREL
LABELING SYSTEMS

7670 Jenther Drive, Mentor, Ohio 44060

440-602-4700 Fax: 440-602-4701 E-Mail: labeling@quadrel.com

Packaging - Processing

Bid on Equipment

1-847-683-7720

www.bid-on-equipment.com