

Identification, Tracking, & Labeling Applications for the Pronto! 472+

- Air and Ground Shipping
- Automotive AIAG Labels
- Circuit Board Identification
- Compliance Labeling
- Cross Dock Reporting
- Electronics EIA Labeling
- Finished Goods inventory
- Fixed Asset Tracking
- Forms Processing
- Invoices and Delivery Documents
- Location Control
- Lot Control
- Pallet Labels
- Quality Control
- Receiving
- Shelf Labeling
- Variable Printing: printing barcodes and text onto pre-printed or blank labels
- Wire Marking
- Warehouse Management
- Work-in-Process Labeling

ONE STOP SHOPPING

QuickLabel manufactures and sells a complete line of printing supplies developed for our line of printers. With our expertise, we are able to recommend thermal transfer ribbon and label combinations that optimize label performance at an economical price. With our deep inventory of paper and synthetic labels and wax, wax-resin, and resin ribbons, we can often provide a same-day shipment.

QUICK LABEL SYSTEMS

PRONTO! 472+ BARCODE PRINTER

Price, Performance and Lifetime Warranty...



QuickLabel refines its barcode printing technology with the Pronto! 472+, offering better features than ever before with the same *lifetime warranty* and *low price* Pronto printers have become known for. Its mission: mid-volume performance printing at office printer pricing.

The Pronto! 472+ reliably prints compliance labels that meet retail and regulatory standards, helping you avoid fines and delays. It even starts you printing custom labels in-house by allowing you to print variable information or barcodes in any single-color onto blank or pre-printed labels.

With faster downloading and processing than similar barcode printers, a heavy-duty printhead that lasts twice as long as the head of similar barcode printers, and a steel body and printing mechanism, the Pronto! 472+ is bred for continuous throughput - even when successive labels require different barcodes and graphics.



The Pronto! 472+ is easy to network with standard USB and optional Ethernet connectivity. It can be networked from any location with its optional WiFi interface - even where network cabling isn't available - so remote users can print and get status reports, all while keeping wire clutter to a minimum.

Prontos are the most comfortable printers to load in the industry. Cover and printhead flip wide open for easy access that reduces ribbon and label loading time to seconds and makes printhead replacement a "snap."



When the stakes are high for compliance labels and product identification, it pays to pick the winner: Pronto! 472+.

It pays to pick the winner.

Packaging - Processing

Bid on Equipment

1-847-683-7720

www.bid-on-equipment.com



¡PRONTO! 472+ BARGODE PRINTER SPECIFICATIONS

PRINT TECHNOLOGY: Direct Thermal, Thermal Transfer

PRINT SPEED: 2-7 ips

PRINT RESOLUTION: 203 dpi

PRINT MODE: Batch, Demand/Peel, Tear, Cut

PRINT WIDTH: 1" to 4.09" (25 mm to 104 mm)

PRINT LENGTH: 0.25" to 32" (6 mm to 813 mm)

CONSTRUCTION: Steel Chassis, Steel Cabinet

BARCODES SUPPORTED: Bookland; Codabar; Code 39, mod 43; Code 93; Code 128 A, B, C, Auto-Switching, F1 Mod 10; EAN-8, Plus 2, Plus 5; EAN-13, Plus 2, Plus 5; EAN-128; HIBCC; IAN; ISSN; Interleaved 2 of 5, 14, 16, mod 10; ISBN; ISDN; JAN; NW-17; Plessey; Postnet; Telepen; UCC 128; UCC/EAN-128, Multi; UPC-A, Plus- 2, Plus 5; UPC-E, Plus 2, Plus 5, Shipping Container;
2-Dimensional: DataMatrix, MaxiCode, PDF 417, QR Code

RESIDENT FONTS: TrueType® scaleable fonts can be downloaded.

Resident fonts include: *CG Triumvirate™* Regular and Bold sizes 6, 8, 10, 12, 14, 18, 24, 30, 36, 48 point; OCR-A, OCR B; 9 alphanumeric System Fonts

FRONT PANEL: Pause, Feed, and Stop buttons. LCD display with Speed, Heat Intensity, and Offset menu functions. LED power and error indicator.

COMMUNICATIONS: USB, RS-232C Serial, and IEEE1284 Parallel Standard. Internal Ethernet and WiFi interfaces optional.

MEMORY: 2 MB DRAM, 1 MB user-available Flash, 1 MB Flash ROM standard

SOFTWARE: Compatible with label creation packages for Windows® and AS/400 environments; Supports major barcode programming languages

DIMENSIONS: 9.9" H x 10" W x 16.9" D (251 mm H x 254 mm W x 428 mm D)

WEIGHT: 24.2 lbs. (11.0 kg)

ENVIRONMENTAL CONDITIONS: *Operating Temperature:* 40.0° F to 120° F (5° C to 49° C); *Humidity:* 30% to 85%, non-condensing

POWER REQUIREMENTS: 120 V, 2.5 Amps or 240 V, 1.25 Amps, 50/60 Hz

AGENCY APPROVALS: UL, CSA, FCC, EN55022, EN55024, EN50082, EN60950, EN61000



LABEL AND RIBBON SUPPLIES:

LABEL MATERIALS:

THICKNESS: 0.0025" to 0.0067" (0.06 mm to 0.25 mm)

WIDTH: 4.65" Maximum (118 mm); 1" Minimum (25 mm)

ROLL OUTSIDE DIAMETER: up to 8" (203 mm) standard

ROLL CORE DIAMETER: 1" to 3" ID (25 mm to 76 mm)

THERMAL TRANSFER RIBBON MATERIALS:

STANDARD WIDTHS: 1.75" (44 mm), 2.25" (57 mm), 2.75" (70 mm), 3.25" (83 mm), 3.75" (96 mm), 4.25" (108 mm)

LENGTH: 1,181 ft. (360 M)

ROLL SIZE: 2.91" (74 mm) OD

OPTIONAL ACCESSORIES:

NiceLabel® software for Windows® and AS/400 Label Creation

External Rewinder

Label/Tag Cutter

Label Peeler: Separates liner from labels On-Demand

QuickNet™ Ethernet Print Server: Allows multiple users to have network print access from major operating systems

**PRICE, PERFORMANCE &
LIFETIME WARRANTY**

www.QuickLabel.com
Call Toll Free: 877.757.7978

QUICK LABEL SYSTEMS
AN ASTRO-MED, INC. PRODUCT GROUP

Manufacturing and Perfecting Thermal Transfer Printers Since 1971.

World Headquarters

600 East Greenwich Ave, West Warwick, RI 02893

toll-free: 877.757.7978 / 401.828.4000

e-mail: info@QuickLabel.com

www.QuickLabel.com

Factory Sales and Service Centers

Canada: 800-565-2216

France: (33) (1) 34 82 09 00

Germany: (49) (6106) 75033

Italy: (39) (02) 2641.1909

United Kingdom: (44) (1628) 668836