

¡PRONTO!

Product Specifications

Printing Method	Thermal Transfer (1 Spot Color) and Direct Thermal
Resolution	304 dpi
Maximum Print Width	5" (127 mm)
Maximum Print Length	48" (122 cm) with Windows® Driver; 24" (61 cm) with Custom QuickLabel®
Print Speed	2" (51 mm) – 15" (254 mm)
Print Modes	Batch, Tear Off, Demand (requires internal rewinder, 4" max OD)
Resident Barcodes	Prints all major barcode symbologies and TrueType® fonts in 304 dpi resolution for optimal barcode scanability and high quality image and text output.
Fonts	7 TrueType resident; other TrueType fonts can be downloaded
Control Panel	Keypad, LCD display and menu functions
Connectivity/Data Interface	PC and AS/400. Standard USB, high-speed parallel IEEE-1284, serial (RS-232), Ethernet (optional)
Software	Custom QuickLabel® for Windows® - Label Creation Software & Windows® Vista/XP/2000/2003 Server Driver Printer Drivers included
Halftoning	MicroCell™ - Individually selectable halftoning for each <i>object</i> ; optimum, coarse, medium, fine, error diffusion, & photographic.
Memory	Standard: 128 MB RAM, 4 Mb image, 4 Mb font, 128 Mb flash memory card. Optional: Up to 512 Mb flash memory card
Encoder	Standard: Improved (1) image placement accuracy and (2) cut accuracy when using cutter accessory.
Dimensions	11" (279 mm) H x 18" (457 mm) D x 15" (381 mm) L
Weight	43 lbs. (19.5 kg) - <i>no media, no ribbons</i>
Power Requirements	120/240 VAC, 50/60 Hz, 3/1.5A

RIBBONS & LABELS

Thermal Transfer Ribbon Supply	1969 ft (600 m) length rolls
Thermal Transfer Ribbon Standard Widths	1.75" (45 mm), 2" (57 mm), 2.75" (70 mm), 3.25" (83 mm), 3.75" (96 mm), 4.25" (108 mm), 4.75" (121 mm), 5.12" (130 mm)
Maximum Label Width	5.125" (130 mm)
Minimum Label Width	.8" (20 mm)
Minimum Label Length	.2" (5 mm)
Label/Tag Thickness	.012" (.305 mm)
Label/Tag Roll Capacity	10" (254 mm) Outside Diameter maximum
GAP	
Maximum Gap Size	1" (25 mm)
Minimum Gap Size	0.07874" (2 mm)
Black Reflective Mark	
Maximum Reflective Mark Size	1" (25 mm)
Minimum Reflective Mark Size	0.07874" (2 mm)
Minimum Length of Reflective Mark	.47" (12 mm) - <i>Extending from Inside Edge of Media</i>



The Labels You Want When You Need Them®

World Headquarters

600 East Greenwich Avenue, West Warwick, Rhode Island 02893

401.828.4000 / toll free 1.877.757.7978

E-mail: printers@QuickLabel.com

Web site: www.QuickLabel.com

©2009 QuickLabel Systems, An Astro-Med, Inc. Product brand Specifications subject to change at anytime without notice.