

## QLS-2000 Specifications

<b>Printing Method</b>	Thermal Transfer, Spot Color
<b>Print Stations</b>	2 independent
<b>Resolution</b>	304 dpi
<b>Maximum Print Width</b>	4.4" (112 mm) from the inside (left) edge of label
<b>Maximum Print Length</b>	44" (111.8 cm) with Windows® Printer Driver; 22" (55.9 cm) with Color QuickLabel 99®
<b>Print Speed</b>	2" (50 mm) –5" (127 mm) per second
<b>Resident Barcodes</b>	All Standard, including 2-D
<b>Fonts</b>	7 TrueType resident; other TrueType fonts can be downloaded
<b>Control Panel</b>	Ergonomic keypad, backlit LCD display and menu functions
<b>Connectivity/Data Interface</b>	PC and AS/400. Parallel ( <i>centronics</i> ) & Serial ( <i>RS-232 &amp; RS-422</i> )
<b>Software</b>	Windows® 95/98/Me/NT/2000/XP Printer Drivers included; Color QuickLabel 99® Pro Label Creation Suite Optional
<b>Halftoning</b>	MicroCell™ - Individually selectable halftoning for each <i>object</i> ; coarse, medium, fine, error diffusion, & photographic.
<b>Memory</b>	<b>Standard:</b> 12 Mb, Image & Font memory are adjustable
<b>Dimensions</b>	20" (508 mm) H x 17" (432 mm) D x 22" (559 mm) L
<b>Weight</b>	84 lbs. (38 kg) - <i>no media, no ribbons</i>
<b>Power Requirements</b>	110/240 VAC, 50/60 Hz, 400W

## RIBBONS & LABELS

<b>Thermal Transfer Ribbon Supply</b>	984 ft (300 m) length rolls
<b>Thermal Transfer Ribbon Standard Widths</b>	1.75" (45 mm), 2" (57 mm), 2.75" (70 mm), 3.25" (83 mm), 3.75" (96 mm), 4.25" (108 mm), 4.75" (121 mm)
<b>Maximum Label Width</b>	4.625" (117 mm)
<b>Minimum Label Width</b>	1" (25 mm)
<b>Minimum Label Length</b>	.395" (10 mm)
<b>Label/Tag Thickness</b>	12 point maximum
<b>Label/Tag Roll Capacity</b>	10" (254 mm) Outside Diameter maximum

### GAP

<b>Maximum Gap Size</b>	3.9" (99 mm)
<b>Minimum Gap Size</b>	0.07874" (2 mm)

### Black Reflective Mark

<b>Maximum Reflective Mark Size</b>	3.9" (99 mm)
<b>Minimum Reflective Mark Size</b>	0.07874" (2 mm)
<b>Minimum Length of Reflective Mark Extending from Inside Edge of Media</b>	.47" (12 mm)



Manufacturing and Perfecting Thermal Transfer Printers Since 1971.

### World Headquarters

600 East Greenwich Avenue, West Warwick, Rhode Island 02893  
 401.828.4000 / toll free 1.877.757.7978  
 E-mail: [printers@quicklabelsystems.com](mailto:printers@quicklabelsystems.com)  
 Web site: [www.quicklabelsystems.com](http://www.quicklabelsystems.com)