



Product Specifications

| | |
|------------------------------------|---|
| Printing Method | Thermal Transfer, Spot Color |
| Print Stations | 2 independent; Two-Sided Printing (1 on the front and 1 on the back) |
| Resolution | 304 dpi |
| Maximum Print Width | 4.4" (112 mm) from the inside (left) edge of label |
| Maximum Print Length | 44" (111.8 cm) with Windows® Printer Driver; 22" (55.9 cm) with Custom QuickLabel® |
| Print Speed | 2" (50 mm) –5" (127 mm) per second |
| Resident Barcodes | All Standard, including 2-D |
| Fonts | 7 TrueType resident; other TrueType fonts can be downloaded |
| Control Panel | Ergonomic keypad, backlit LCD display and menu functions |
| Connectivity/Data Interface | PC and AS/400. Parallel (<i>centronics</i>) & Serial (<i>RS-232 & RS-422</i>) |
| Software | Windows® Vista/XP/2000/2003 Server Driver Printer Drivers included; Custom QuickLabel® Label Creation Suite Optional |
| Halftoning | MicroCell™ - Individually selectable halftoning for each <i>object</i> ; coarse, medium, fine, error diffusion, & photographic. |
| Memory | 128 Mb RAM; 512 Mb FLASH Memory Card included; Up to 2 Gb FLASH Memory Card <i>Optional</i> |
| Dimensions | 20" (508 mm) H x 17" (432 mm) D x 22" (559 mm) L |
| Weight | 84 lbs. (38 kg) - <i>no media, no ribbons</i> |
| Power Requirements | 110/240 VAC, 50/60 Hz, 400W |

RIBBONS & LABELS

| | |
|--|--|
| Thermal Transfer Ribbon Supply | 984 ft (300 m) length rolls |
| Thermal Transfer Ribbon Standard Widths | 1.75" (45 mm), 2" (57 mm), 2.75" (70 mm), 3.25" (83 mm), 3.75" (96 mm), 4.25" (108 mm), 4.75" (121 mm) |
| Maximum Label Width | 4.625" (117 mm) |
| Minimum Label Width | 1" (25 mm) |
| Minimum Label Length | .395" (10 mm) |
| Label/Tag Thickness | .012" (.305 mm) |
| Label/Tag Roll Capacity | 10" (254 mm) Outside Diameter maximum |
| GAP | |
| Maximum Gap Size | 3.9" (99 mm) |
| Minimum Gap Size | 0.07874" (2 mm) |
| Black Reflective Mark | |
| Maximum Reflective Mark Size | 3.9" (99 mm) |
| Minimum Reflective Mark Size | 0.07874" (2 mm) |
| Minimum Length of Reflective Mark Extending from Inside Edge of Media | .47" (12 mm) |



The Labels You Want When You Need Them®

World Headquarters

600 East Greenwich Avenue, West Warwick, Rhode Island 02893
 401.828.4000 / toll free 1.877.757.7978

E-mail: info@QuickLabel.com

Web site: www.QuickLabel.com

©2009 QuickLabel Systems, An Astro-Med, Inc. brand
 Specifications subject to change at anytime without notice.