

Range Boss Specifications

Printing Method	Thermal Transfer (1 Spot Color) and Direct Thermal
Resolution	304 dpi
Maximum Print Width	8.5" (216 mm)
Maximum Print Length	14" (356 mm)
Print Speed	3" (76 mm) – 6" (152 mm) per second
Resident Barcodes	Prints all major barcode symbologies and TrueType® fonts in 304 dpi resolution for optimal barcode scannability and high quality image and text output.
Fonts	7 TrueType resident; other TrueType fonts can be downloaded
Control Panel	Keypad, backlit LCD display and menu functions
Connectivity/Data Interface	PC and AS/400. Parallel (<i>centronics</i>) & Serial (<i>RS-232</i>)
Software	Standard: Windows® 95/98/Me/NT and 2000 Printer Drivers Optional: Color QuickLabel 99® Pro for Windows® - Label Creation Software
Halftoning	MicroCell™ - Individually selectable halftoning for each <i>object</i> ; coarse, medium, fine, error diffusion, & photographic.
Memory	Standard: 4 Mb, 128 kb Image, 256 kb Font Optional: Up to 4 Mb Ram Card (<i>PCMCIA Type 1</i>)
Dimensions	15.5" (394 mm) H x 17.75" (450 mm) D x 19.5" (495 mm) L
Weight	55 lbs. (25 kg) - <i>no media, no ribbons</i>
Power Requirements	120/240 VAC, 50/60 Hz, 240 W

RIBBONS & LABELS

Thermal Transfer Ribbon Supply	1969 ft (600 m) length rolls
Maximum Label Width	8.5" (216 mm)
Minimum Label Width	4.5" (114 mm)
Minimum Label Length	.2" (5 mm)
Label/Tag Thickness	12 point maximum
Label/Tag Roll Capacity	8" (203 mm) Outside Diameter maximum



Manufacturing and Perfecting Thermal Transfer Printers Since 1971.

World Headquarters

600 East Greenwich Avenue, West Warwick, Rhode Island 02893

401.828.4000 / toll free 1.877.757.7978

E-mail: printers@quicklabelsystems.com

Web site: www.quicklabelsystems.com