



Product Specifications

Printing Technology	Thermal Inkjet
Resolution	4800* x 1200 dpi, 600 x 600 dpi, 300 x 300 dpi * virtual resolution
Print Area	
Width	1.5" - 8.375" (8.5" total construction) 1" with optional label flange
Length	1.0" - 24.0" <i>Narrower labels can be printed multiple-across</i>
Ink Cartridges	
Color	QuickLabel Zeo! CMY Color Cartridge, 17 mL dye-based
Black	QuickLabel Zeo! Black Cartridge, 19 mL pigment-based
Label Media	
Types	High-Gloss, Semi-Gloss, and Matte Paper pressure-sensitive; Synthetic pressure-sensitive; Paper Tag Stock
Roll	6" OD (152 mm) QuickLabel paper and synthetic labels on 3" ID core
Z-Fold	3" maximum pack height
Media Sensing	Gap, Reflective, and Continuous. Adjustable sensor to 4.28"
Image Placement	±0.5 mm, down-web and cross-web
Software	Custom QuickLabel® Photo label creation and print management program suite included Zeo! Windows® Vista/2000/XP Driver included
Minimum System Requirements	Pentium III / 4 or equivalent, 256 Mb RAM, 50 Mb hard drive space, CD-ROM or DVD drive, Two available USB ports for Zeo! and Custom QuickLabel® Photo
Control Panel	Ergonomic Keypad for menu functions, Two-line x 16-character LCD Display
Connectivity	USB 2.0
Environment	Office Environment
Operating Temperature	59°F to 95°F (15°C to 35°C)
Non-Operating Temperature	23°F to 104°F (-5°C to 40°C)
Operating Humidity	20% to 80% Relative Humidity, non-condensing
Dimensions	8.8" H x 19" D x 20" L (22.4 cm H x 48.3 cm D x 50.8 cm L)
Weight	28.4 Lbs. (12.9 Kg)
Power Requirements	Input: 90 - 264VAC autoswitching, 50/60 Hz, 60W max
Safety and EMI Certifications	ETL C/US, CE, FCC Part 15 Class B, RoHS compliant
Optional Accessories	Zeo! Automatic Label Roll Rewinder, Label Dispenser



The Labels You Want When You Need Them®

World Headquarters

600 East Greenwich Avenue, West Warwick, Rhode Island USA 02893
 401.828.4000 / toll free 877.757.7978
 E-mail: info@QuickLabel.com
 Web site: www.QuickLabel.com