

# D508/512

## High-Volume Desktop Printer



### Streamlined Features

- High Print Speed – up to 6 ips
- 305 dpi (203 dpi Optional)
- SATO and PCL5e Subset Programming Languages
- Cost Effective Direct Thermal
- Easy View Media Window
- Clamshell Design
- High Lift Print Head
- USB Interface (standard)

### Industry Verticals

- Logistics
- Manufacturing
- Distribution
- Pharmaceutical & Healthcare
- Retail
- Transportation
- Apparel
- Automotive
- Military/DoD

### Industry Applications

- Pharmacy Labeling
- Wristband Printing
- Asset Labeling
- Retail Marking
- Shipping/Receiving
- Compliance Labeling
- Healthcare Patient I.D.
- Product ID Labeling

PRINTER MODEL		D508	D512
<b>PRINT SPECIFICATIONS</b>			
Print Method		Direct Thermal	
Print Resolution		203 dpi (8 dot/mm)	305 dpi (12 dot/mm)
Print Speed		6 ips (150 mm/second)	4 ips (100 mm/second)
Max. Print Area		4.1" (104 mm) W x 15.7" (400 mm) L	
<b>MEDIA SPECIFICATIONS</b>			
Sensor Type		Reflective Sensor (for use with pre-printed I-marks) See-Through Sensor (for die-cut label with gap) Sensor not used - Continuous	
Media Type		Roll and Fanfold	
Media Size	Width	1.1" (28 mm) - 4.65" (118 mm)	
	Length (Continuous)	0.71" (18 mm) - 15.75" (400 mm)	
	Length (Tear Off)	0.71" (18 mm) - 15.75" (400 mm)	
	Length (Cutter - opt.)	1.1" (28 mm) - 15.75" (400 mm)	
	Thickness	0.002" (0.06 mm) - 0.007" (0.19 mm)	
	Roll Specs	4.33" (110 mm) Outer Diameter; 1.5" (40 mm) Inner Diameter	
	Wind Orientation	Face-out	
<b>FONT / SYMBOLOGIES</b>			
Printer Command Language		SATO and PCL5e Subset	
SATO Printer Command Language (for 203 dpi and 305 dpi)	Font	U, S, M, WB, XS, XU, XM, XB, XL, OUTLINE, OCR-A, OCR-B, WL, CG Times, CG Triumvirate	
	Linear Barcode	UPC-A, UPC-E, EAN-8, EAN13, Code 39, Code 93, Code 128, Codabar, MSI, Bookland, Industrial 2/5, Interleaved 2/5, Matrix 2/5, Postnet, UCC/EAN 128, RSS Composite Code	
	2-D Barcode	PDF417, Micro PDF417, Truncated PDF417, Maxicode, Data Matrix, QR Code	
PCL5e Subset (Optional for 305 dpi only)	Font	CG Triumvirate Bold Condensed Bold, Univers Medium, Univers Bold, Courier Regular, OCR-A, OCR-B, Roman Pillar Regular, Roman Pillar Bold, Roman Pillar Italic, Roman Pillar Bold Italic (supports Universal Font Scaling Technology Ver.4.1)	
	Linear Barcode	UPC-A, UPC-E, EAN-8, EAN13, Code 39, Code 93, Code 128, MSI, Bookland, Industrial 2/5, Interleaved 2/5, Matrix 2/5, Postnet, UCC/EAN 128	
	2-D Barcode	PDF417, Maxicode	
<b>COMMUNICATION INTERFACE</b>			
Interface Options		USB, IEEE1284, Serial RS232 (up to 57.6k bps), Ethernet - 10/100BaseT (internal), Wi-Fi - 802.11b/g (internal)	
<b>OPERATING CHARACTERISTICS</b>			
Power Requirements		100-120V, 50/60 Hz	
Environment	Operating	32° to 95°F (0° to 35°C), 30-80% RH, non-condensing	
	Storage	23° to 140°F (-5° to 60°C), 30-90% RH, non-condensing	
Dimension		7.8" (198 mm) W x 9.1" (230 mm) D x 6.6" (167 mm) H	
Weight		5.5 lbs (2.5 Kg) excluding AC adaptor	
<b>OPTIONS</b>			
Label Cutter (factory installed), Label Gallery Software, optional 110-220V Auto-Switching Power Supply			

All company and/or product names are trademarks and/or registered trademarks of their respective owners. The acronyms used to identify non-SATO programming languages are used only for explanation without intent to infringe. SATO makes no claim to the authenticity of non-SATO command languages or functionality. Specifications are subject to change without notice.

### SATO America, Inc.

10350-A Nations Ford Road, Charlotte, NC 28273

Phone: (704) 644-1650 Fax: (704) 644-1662

E-mail: sato-sales@satoamerica.com

© 2008 SATO America, Inc. All rights reserved. Rev. 11/08b