


Lt408 OEM Print Engine

Durability & Performance in an Economical OEM Package



Large-LCD display and icon-driven user interface makes operation easy and intuitive



One-Touch release makes printhead change fast and easy



Bi-directional ribbon drive offers greater ribbon compatibility



Utilizes SATO Program Language...the industry leader in print apply applications



Plug-in interface design for communication flexibility and SATO multi-platform compatibility

MODEL		Lt408 OEM Print Engine
PRINTING SPECIFICATION		
Print Method		Direct Thermal/Thermal Transfer
Print Resolution		203 dpi (8 dpmm)
Print Speed		2 to 6 ips (50 to 150mm/s)
Max. Print Area		4.09" (104mm) W x 49.2" (1,249mm) L
MEDIA SPECIFICATION		
Sensor Type		Reflective Sensor (for use with pre-printed marks) Adjustable See-Through Sensor (for die-cut label with gap)
Media Type		Die-Cut Labels, Waste Removed, Roll, 0.125" gap
Media Size	Width	1.125" - 4.52" (28.6mm - 115mm)
	Length	0.6" - 49.2" (15mm - 1,249mm)
	Thickness	0.003" - 0.010" (0.08mm - 0.26mm)
	Outer Diameter	max. 12" (305mm) Unwind Roll - Applicator Specification
Ribbon (CSI/CSO)	Width	0.98" - 4.37" (25mm - 111mm)
	Length	Up to 1476' (450 m)
MEMORY		
Processor		32-bit RISC
Memory		4MB Flash ROM / 16MB SDRAM
Receive Buffer		max. 2.95MB
FONT / SYMBOLOGIES		
Internal Fonts	Standard Fonts	XU, XS, XM, XB, XL, Outline, OCR-A, OCR-B
	TrueType Fonts	CG Times (Serif), CG Triumvirate (San Serif)
Barcode Symbologies	Linear	UPC-A/E, JAN/EAN-8/13, UCC/EAN-128, Interleaved 2 of 5, Code 39, Code 93, Code 128, Matrix 2 of 5, RSS-14, NW-7 (Codabar), POSTNET, MSI, Bookland
	2-Dimensional	Data Matrix, PDF417, Maxicode, QR Code, Composite Symbology
INTERFACE CHARACTERISTICS		
Standard (choose one)		IEEE1284 (Parallel); RS232C Serial (25-pin)
Interface Options		LAN (10BaseT/100BaseTX auto-switching), Wireless LAN (802.11g), RS422/485
EXT Port (Applicator Interface)		14-Pin Centronics style connector
OPERATING CHARACTERISTICS		
Power Requirements		100 - 240 VAC (+/- 10%); 50/60 Hz; Auto-Switching
Environment	Operating	41° - 104°F (5° - 40°C); 15% - 85% RH, non-condensing
	Storage	0° - 140°F (-20° - 60°C); 15% - 85% RH, non-condensing
Regulatory Approvals		FCC Class B, MET (UL60950-1/CSA60950-1), CE
Dimensions		13" W x 10.7" D x 10.6" H (330mm W x 271mm D x 270mm H) Weight: 21.4 lbs. (9.7Kg) Standard Configuration

*Specifications subject to change without notice

Label Gallery 2 - Label Design Software

Label Gallery is a unique label design and production suite of software based on an easy-to-use and intuitive user interface designed specifically for SATO Printers. Label Gallery offers a family of professional labeling software products including a multi-lingual user interface and complete barcode printing solutions for desktop and enterprise users.

LG EASY - Entry-Level

- Entry-level Labeling Software
- **NEW** – Unicode Label Design
- Wizard-Based Basic Barcode Labeling



LG PLUS - Advanced

- Advanced & Compliance Label Design
- RFID Support (HF & UHF/EPC)
- Complete Database Support
- Programming Integration Option
- ActiveX Programming Interface
- Downloading to Memory
- VB Scripting



LG TRUE PRO with WinCE

- Advanced & Compliance Label Design
- RFID support (HF & UHF/EPC)
- Middleware Integration Module
- Creating Standalone Label Applications
- Non-Windows & Stand-Alone Printing
- Mobile Wireless Printing (WinCE support)



SATO America, Inc.

10350-A Nations Ford Road, Charlotte, NC 28273
Phone: (704) 644-1650 Fax: (704) 644-1662
E-mail: satosales@satoamerica.com