

# Automatic Steel Strapping Systems

Models  
M200,  
M220

 SIGNODE

**T**wo Signode® power strapping machines —Models M200 and M220—are ideal for automatic packaging of high density loads where the strength of steel strapping is necessary.

## Consider the Advantages

A step up from strapping your packages manually, our M200 and M220 power strapping machines help you increase productivity by adding just the amount of automation you need to keep pace with your production schedules.

And you'll build more secure, manageable loads because the adjustable tension capability of both machines allows you to pull the exact amount of tension needed.

## Versatility

Both power strapping machines are available in 56 standard chute sizes for versatility in strapping packages from 12" (304.8 mm) high and 12" (304.8 mm) wide to 48" (1.2 m) high and 54" (1.4 m) wide, in 6" (152.4 mm) increments.

## Ease of Maintenance, Repair

Models M200 and M220 have modular components that make for easy maintenance, trouble-shooting and repair. Other benefits include:

- Nickel plated strapping chute to resist corrosion.
- Stainless steel gates for durability, rust prevention.
- Heavy gauge bar for chute alignment support.

## Ease of Operation

An operator simply positions a package in the chute and activates a footswitch, to automatically apply, tension, seal and cut the steel strapping. Material waste is eliminated because no extra strap has to be cut off and discarded.

## Use Nestack® Seals

Magazines of both power strapping machines accept Signode Nestack seals, held together in a clip by interlocking nibs on the seals rather than by a separate wire. This permits partial seal loading when desired.

## For medium-duty, high volume strapping applications

The M200 incorporates the proven M20 steel strapping head into a new machine, with versatility and space saving features that make it ideal for a fully automated operation. Tension can be set from 50-1200 lbs. (233-5430 N) for packaging loads that require the strength of steel strapping.

The M200 uses the following types and sizes of Signode steel strapping:

Strapping Type	Strapping Width		Thickness or Gauge	
	inches	mm	inches	mm
Apex™	3/8	9.5	.015-.020	.381-.508
Apex or Magnus®	1/2	12.7	.015-.023	.381-.584
	5/8	15.9	.015-.023	.381-.584
	3/4	19.0	.015-.035	.381-.889



**SIGNODE MODEL**

**M200**

Packaging - Processing

**Bid on Equipment**

1-847-683-7720

[www.bid-on-equipment.com](http://www.bid-on-equipment.com)

