



Non-Slamming HTST Divert Valve

Model W265FD & Aseptic Model W285FD

1 inch through 4 inch



- New lower body streamlined for improved flow path and cleanability
- Flush Ports for easy cleaning
- Compact vertical design
- Works with existing control system
- High temperature Tef-lo P seats
- Transparent Control Top
- Top with or without Solenoid
- Maintainable Actuator
- 4-inch, 5-inch, or 6-inch actuators
- S, I, or Q clamp connections
- Body clamps standard "S" style

**ISO 9001
CERTIFIED**



SPX Process Equipment, 611 Sugar Creek Road, Delavan, WI 53115
Phone: (262) 728-1900 or (800) 252-5200 Fax: (262) 728-4904 or (800) 252-5012
E-mail: wcb@spx.com

For more information about our worldwide locations, approvals, certifications, and local representatives, please visit www.spxpe.com.

SPX reserves the right to incorporate our latest design and material changes without notice or obligation.

Design features, materials of construction and dimensional data, as described in this bulletin, are provided for your information only and should not be relied upon unless confirmed in writing.

Issued: 02/2009 FH-1863

Copyright © 1997, 2008 SPX Corporation

Packaging - Processing
Bid on Equipment
1-847-683-7720
www.bid-on-equipment.com