

## Batch Series Finishing Mills



### FM-1.2C

<b>Capacity</b>	1.2 ft <sup>3</sup> (300 lbs. load capacity)
<b>Maximum Straight Part Length</b>	9 inches
<b>Motion Generator</b>	1/3 hp, TENV, 1200 RPM, single phase 115 volt; 3-phase 230, 460 or 575 volt. 60 Hz.
<b>Vibralite Bowl</b>	Chamber - all cast polyurethane elastomer with 3/4" minimum thickness in high wear areas
<b>Shipping Weight</b>	210 lbs. (empty)

### FM-3C & FM-3HA

<b>Capacity</b>	3 ft <sup>3</sup> (900 lbs. load capacity)
<b>Maximum Straight Part Length</b>	12 inches
<b>Motion Generator</b>	1 1/4 hp, TENV, 1200 RPM, 3-phase 230, 460, or 575 volt. 60 Hz.
<b>Lining</b>	5/16" Cast Polyurethane Elastomer
<b>Shipping Weight</b>	Approximately 550 lbs.

## FM-10V & FM-10C

<b>Capacity</b>	10 ft <sup>3</sup> (3000 lbs. load capacity)
<b>Maximum Straight Part Length</b>	24 inches
<b>Motion Generator</b>	5 hp, TENV, 1200 RPM, 3-phase 230, 460, or 575 volt. 60 Hz.
<b>Lining</b>	¾" Cast Polyurethane Elastomer
<b>Shipping Weight</b>	Approximately 1175 lbs.

Model FM-10C available with curved outer chamber wall.

## FM-20HA

<b>Capacity</b>	20 ft <sup>3</sup> (6000 lbs. load capacity)
<b>Maximum Straight Part Length</b>	30 inches
<b>Motion Generator</b>	10 hp, TENV, 1200 RPM, 3-phase 230, 460, or 575 volt. 60 Hz.
<b>Lining</b>	¾" Cast Polyurethane Elastomer
<b>Shipping Weight</b>	Approximately 2500 lbs. (including control panel)