


Model 9000



Model 9000* - Random length cold seal machine specifically designed for mailing applications

The 9000 random length machine is equipped with indexing feed fingers to speed the handling and loading of rectangular items such as books, CD's, etc. It accepts a continuous stream of products varying in length, and adjusts the package length accordingly. Speed will vary by length of package and by the feed rate of products. Long or irregular shaped products can be accommodated with an optional belted infeed conveyor.

The system uses paper, polyethylene, single-face corrugate, and paper microfoam laminate in any combination.



SYSTEM PACKAGING

*Machine pictured with optional friction feeder, cassette feeder, and quick-change pneumatic spindles.

Model 9000


SPECIFICATIONS

Model	DIMENSIONS			PACKAGE SIZES			STANDARD ELECTRICAL REQUIREMENT	STANDARD AIR REQUIREMENT
	L	D	H	Min.	Max.	Max. Ht.		
9000-18	190"	60"	87"	4" x 6"	18" x 20"	5"	115 VAC, Single Phase, 15 AMPS	6 CFM @ 80 PSI
9000-24	190"	66"	87"	10" x 10"	24" x 20"	5"	115 VAC, Single Phase, 15 AMPS	6 CFM @ 80 PSI
9000-24-8	196"	66"	87"	10" x 10"	24" x 20"	8"	115 VAC, Single Phase, 15 AMPS	11 CFM @ 80 PSI
9000-36	214"	80"	87"	10" x 10"	36" x 96"	8"	115 VAC, Single Phase, 15 AMPS	9 CFM @ 80 PSI

Note: Dimensions, requirements and package length can change with system additions.

FEATURES:


- ▶ Unit speed is up to 35 packages per minute for 6" length package
- ▶ 8' - five station infeed conveyor with polished stainless steel tabletop
- ▶ 3' exit conveyor
- ▶ 5" maximum package height
- ▶ Touch-screen control panel
- ▶ Powered pull roll tire adjustment
- ▶ NEMA 12 electrical enclosure
- ▶ Polished stainless steel infeed surface



Custom designs and programs to meet your needs

OPTIONS:

- ▶ Single or multiple friction feeders for automatic collating
- ▶ Belted infeed conveyor for long or irregular shapes
- ▶ Adjustable hopper/feeders for books, CD's, videos, and cassettes
- ▶ Scan, Print, and Apply systems
- ▶ Vacuum label transfer conveyors
- ▶ Perforators for easy open packages
- ▶ Quick-change pneumatic spindles for material
- ▶ Random height product detection with automatic package length adjustment
- ▶ Inline Weighing and Sortation systems



Purchase of some options may change specifications and requirements



SYSTEM PACKAGING

28905 GLENWOOD ROAD • P.O. BOX 109
 PERRYSBURG, OHIO 43552-0109
 419/666-9712 • FAX 419/666-8072
 E-MAIL: sales@systempackaging.com

A Division of Glassline Corporation

