

Fixed Gas Monitoring System, Model 128™

Wall-mounted, local area monitor for one to eight sensors



Key Features

- Accepts from one to eight remote sensors
- Unique built-in calibration reminder
- Auto-Install feature simplifies set-up
- Easy plug in electrochemical sensor replacement
- Reduces installation cost through digital communication
- Housed in a weather-tight fiberglass enclosure

The Thermo Scientific Fixed Gas Monitoring System, Model 128 is a wall mounted gas monitor designed for reliable gas detection, easy installation and low total cost of ownership.

The Model 128 is a cost-effective solution for warning of unsafe gas levels in areas such as semiconductor manufacturing, wastewater treatment, garages, warehouses, toll booths, gas bunkers, utilities and telecom industries.

The Model 128 accepts from one to eight combustible, oxygen, and/or toxic sensors. Each sensor provides a digitized output, allowing easy and economical networking of multiple sensors.

Other Features include:

- 19 available sensors that can be factory-configured or configured in the field
- Super bright LED array provides quick indication of normal, fault and alarm conditions
- One-person calibration
- Loud audible alarm (98 dB)
- Combustible gas sensors are mounted in an explosion proof housing
- Non-intrusive calibration for combustible sensor
- Outstanding protection from EMI / RF interference
- Common programmable internal relays for Low, High and Fail alarms
- Intrinsically safe oxygen and toxic gas sensors available
- Easy to follow instructions for calibration, alarm setting, concentration values and programming
- User configurable alarms

To maintain optimal product performance, you need immediate access to experts worldwide, as well as priority status when your air quality equipment needs repair or replacement. We offer comprehensive, flexible support solutions for all phases of the product life cycle. Through predictable, fixed-cost pricing, our services help protect the return on investment and total cost of ownership of your Thermo Scientific air quality products.

Product Specifications

Sensors	Toxic / O ₂ : Intrinsically safe for Class I Groups A, B, C & D area (optional)
Area Classification	General Purpose (controller)
Combustible	Explosion proof, suitable for Class I, Groups B, C & D hazardous
Inputs	One to eight remote sensors
Current Consumption	0.2 A protected by a 0.5 A fuse
Operating Temperature	-4°F to 122°F (-20°C to 50°C)
Humidity	0 to 95% RH, non-condensing
User Interface	
Low Alarms	User programmable, latching or non-latching, energized or de-energized and alarm delay
High Alarms	User programmable, energized or de-energized and alarm delay
Audible Alarm	98 dB @ 1ft. (30cm)
Display	Internally mounted 16 x 2 character backlight LCD
Programming	Five buttons: Run, Enter, Up, Down, Reset
Internal Relays	Common Low, High and Fault alarms, form C contacts rated at 5 Amps/250 VAC
Input Power	100/130 VAC 50/60 Hz, 200/260 VAC 50/60 Hz (optional)
Construction	
Dimensions	10" (L) x 8" (W) x 6" (H) 254mm (L) x 203mm (W) x 152mm (H)
Weight	8 lbs. (3.6 kg)
Case Materials	NEMA 4X fiberglass polyester
Calibration	
Time Out	User adjustable from OFF to 100 minutes
Reminder	User adjustable from OFF to 180 days
Approvals	CSA Approved and NRTL Classification
Warranty	One year (materials and workmanship)

Gas	Formula	Standard Range
Ammonia	NH ₃	0 to 100 ppm in 1 ppm increments
Arsine	AsH ₃	0 to 1.00 ppm in 1 ppm increments
Carbon Monoxide	CO	0 to 500 ppm in 1 ppm increments
Chlorine	Cl ₂	0 to 10.0 ppm in 0.1 ppm increments
Chlorine Dioxide	ClO ₂	0 to 2.00 ppm in 0.01 ppm increments
Combustible	several	0 to 100% LEL in 1% LEL
Diborane	B ₂ H ₆	0 to 1.00 ppm in 0.01 ppm increments
Fluorine	F ₂	0 to 10.0 ppm in 0.1 ppm increments
Hydrogen Chloride	HCl	0 to 30.0 ppm in 0.1 ppm increments
Hydrogen Cyanide	HCN	0 to 50.0 ppm in 0.1 ppm increments
Hydrogen Fluoride	HF	0 to 10.0 ppm in 0.1 ppm increments
Hydrogen Sulfide	H ₂ S	0 to 100 ppm in 1 ppm increments
Nitric Oxide	NO	0 to 20.0 ppm in 0.1 ppm increments
Nitrogen Dioxide	NO ₂	0 to 100 ppm in 1 ppm increments
Oxygen	O ₂	0 to 30.0% Vol. in 0.1% increments
Ozone	O ₃	0 to 1.0 ppm in 0.1 ppm increments
Phosphine	PH ₃	0 to 1.0 ppm in 0.1 ppm increments
Silane	SiH ₄	0 to 50.0 ppm in 0.1 ppm increments
Sulfur Dioxide	SO ₂	0 to 10.0 ppm in 0.1 ppm increments

This specification sheet is for informational purposes only and is subject to change without notice. Thermo Fisher Scientific makes no warranties, expressed or implied, in this product summary.
© 2009 Thermo Fisher Scientific, Inc. All rights reserved Thermo Fisher Scientific, Inc.

This product is manufactured in a plant whose quality management system is ISO 9001 certified.

**Environmental
Instruments Division**
Air Quality Instruments

27 Forge Parkway
Franklin, MA 02038 USA

(866) 282-0430
(508) 520-0430
(508) 520-1460 fax

www.thermo.com/ih

Lit_128AQI_08/09

Thermo
SCIENTIFIC