

Our Revco laboratory refrigerators and freezers are an economical choice for common non-critical laboratory requirements. Models provide dependable refrigeration systems and quality cabinet construction with basic control features.

Thermo Scientific Revco General Purpose Refrigerators, Freezers and Combinations



Refrigerators and Combinations

- Refrigerator operating temperature: +2°C to +10°C
- Freezer operating temperature: -12°C to -18°C
- High-strength shelves with interior door shelving for added inventory capacity
- Hermetically-sealed compressor for quiet operation, CFC-free refrigerants
- Built-in condensate drain on 20.7 cu. ft. models
- Magnetic door gaskets for positive seal; 20.7 cu. ft. models feature keyed door lock
- Power cord and plug provided for all models with 115V, 60Hz operation; NEMA 5-15R/5-15P
- Durable, white acrylic exterior finish and seamless interior

Laboratory Freezers

- Adjustable operating temperature: -12°C to -20°C
- High-strength shelves plus door shelving for increased storage capacity
- Hermetically-sealed compressor for quiet operation, CFC-free refrigerants
- High-density urethane foam insulation
- Magnetic door gaskets for positive seal; 20.7 cu. ft. models feature keyed door lock
- Power cord and plug provided for all models with 120V, 60Hz operation, NEMA 5-15R/5-15P
- Durable, white acrylic exterior finish and seamless interior

Thermo Scientific Revco General Purpose Refrigerators

Operating Temperature Range: +2°C to +10°C (manual defrost)

| Model No. | Cu.Ft. (L) | Voltage (Hz) | Amps/ Breaker (Plug) | Shelves - Interior (Shelves - Door) | Interior Dimensions* H x D x W inches (mm) | Exterior Dimensions* H x D x W inches (mm) | Ship Weight lb (kg) |
|-----------|---------------|--------------|-------------------------|--|---|---|------------------------|
| RLR2111A | 20.7 (586) | 120 (60) | 5/15 (5-15R/5-15P) | 4 (6) | 57.5 x 23.5 x 27.0 (1460 x 600 x 690) | 70.2 x 30.2 x 32 (1800 x 770 x 810) | 250 (114) |

Thermo Scientific Revco General Purpose Refrigerator/Freezer Combinations

Operating Temperature Range: +2°C to +10°C, Freezer -12°C to -18°C (manual defrost)

| Model No. | Cu.Ft. (L) | Voltage (Hz) | Amps/ Breaker (Plug) | Shelves - Interior (Shelves - Door) | Interior Dimensions* H x D x W inches (mm) | Exterior Dimensions* H x D x W inches (mm) | Ship Weight lb (kg) |
|-----------|----------------------------|--------------|-------------------------|--|---|---|------------------------|
| RCRF112A | 8.6/244 (ref) | 120 (60) | 3.8/15 (5-15R/5-15P) | 4 (6) | ref: 35.3 x 19 x 20 (900 x 480 x 510) | 58.8 x 25.8 x 23.5 (1490 x 660 x 600) | 182 (83) |
| | 2.4/68 (frz) | | | | frz: 13 x 18 x 17.5 (330 x 460 x 440) | | |
| RCRF252A | 17.5/496 (ref) | 120 (60) | 5.7/15 (5-15R/5-15P) | 4 (6) ref 1 (2) frz | ref: 37.8 x 24.5 x 32 (960 x 620 x 810) | 68.6 x 33.6 x 36 (1740 x 850 x 910) | 142 (64) |
| | auto defrost 7.1/201 (frz) | | | | frz: 18.8 x 20.5 x 31 (480 x 520 x 790) | | |

Thermo Scientific Revco General Purpose Freezers

Operating Temperature Range: -12°C to -18°C (manual defrost)

| Model No. | Cu.Ft. (L) | Voltage (Hz) | Amps/ Breaker (Plug) | Shelves - Interior (Shelves - Door) | Interior Dimensions* H x D x W inches (mm) | Exterior Dimensions* H x D x W inches (mm) | Ship Weight lb (kg) |
|-----------|---------------|--------------|-------------------------|--|---|---|------------------------|
| REF417A | 5.0 (141) | 115 (60) | 5/15 (5-15R/5-15P) | 2 | 29 x 19 x 20 | 34 x 21 x 27 | 84 |
| | | | | (3) | (737 x 476 x 495) | (851 x 540 x 673) | (38) |
| REF1617A | 17.3 (490) | 120 (60) | 1.8/15 (5-15R/5-15P) | 3 | 51.5 x 21.5 x 27 | 65.2 x 28 x 32 | 235 |
| | | | | (5) | (1310 x 550 x 690) | (1660 x 710 x 810) | (107) |
| REF2117A | 20.7 (586) | 120 (60) | 1.8/15 (5-15R/5-15P) | 4 | 57 x 23 x 27 | 70.2 x 30.2 x 30 | 250 |
| | | | | (6) | (1450 x 580 x 690) | (1780 x 770 x 810) | (114) |

*All dimensions and specifications subject to change without notice. External dimensions include allowances for cabinet door, hinges, latches, handles, and control panel protrusions. ¹No plug provided; requires hardwire connection by customer.

