

Packaging - Processing

Bid on Equipment

1-847-683-7720

www.bid-on-equipment.com

Model 1318

Manual Bandsaw

formerly model 1118


**13" Capacity Wet Cutting
Hydraulic Feed Variable Bandspeed**



**WELLSAWS work harder and last longer
because they are built better.**

Wellsaw®

2829 N. Burdick St.
Kalamazoo MI 49004
Phone 269-345-1132
Fax 269-345-0095
www.wellsaw.com



Model 1318 Manual Bandsaw

formerly model 1118

Manufactured in the United States of America

Standard Features:

Spring loaded Carbide Guides with Rollers
Combination Reduction Gearbox and
Ring & Pinion Blade Drive
Baldor® Motor
 3 HP Motor 3 Phase TEFC
 2 HP Single Phase ODP
Infinitely Variable Blade Speeds
Rite-Tension® Blade Tensioning Device
Wet Cutting System
Powered Blade Brush
110 Volts at Controls
Overload and Undervoltage Protection
Precision Ground Bed and Vise Jaws
Quick Acting Vise
Adjustable Stock Stop
Auto Shut-Off at End of Cut
OSHA Blade Guarding
Tiger-Tooth® Bi-Metal Blade
Coolant for Initial Start-Up

Specifications:

Capacity	Round 13" Rectangular 13" x 18" 45° Angle 11" x 9 1/2"
Blade Size	1" x .035" x 12'- 6" (150")
Blade Speeds	Infinitely Variable 70 - 375 SFPM
Blade Guides	Carbide Guides with Rollers
Blade Tension	Manual Rite-Tension®
Electrical Options	115-208-230/60/1 208-230-460/60/3
Coolant System	Tank Capacity 8 gallons Submersible Pump / 3 gpm
Vise Control	Quick Acting / Manual Screw To 45°
Swivel Vise	
Feed Control	Variable Hydraulic / Counterbalance Spring
Band Wheels	15" Diameter Cast Iron
Bed Height	29"
Floor Area	40"W x 84"L
Shipping Weight	955 lbs.

Factory Installed Options Available

Flush Hose w/ 8.5 gpm pump
Powered Frame Raise and/or Powered Vise
Laser Line Pointer
Casters (Set of 4, 2 Locking)
NFPA Electrics (w/disconnect)
Work Light w/ transformer
Stock Stand, 18"
5' Non-Powered Roller Conveyor
10' Non-Powered Conveyors
Please Contact Factory For Additional Options

Other Models in the 1318 Family

Model 1338 with 38" width capacity
Model 1316S Swivel Head Miter Saw to 60 degrees
All models available w/ PLC controlled Semi-Automatic
Operation

Specifications Subject to Change Without Notice



2829 N. Burdick St.
Kalamazoo, MI 49004
Phone 269-345-1132
Fax 269-345-0095
Email info@wellsaw.com