

# Model 1338

## Manual Bandsaw with Extended Capacity


13" x 38" Capacity

Ideal for floor gratings, roofing panels, structural shapes, and other light to medium duty applications.



**Wellsaw**®

2829 N. Burdick St.  
Kalamazoo MI 49004  
Phone 269-345-1132  
Fax 269-345-0095  
www.wellsaw.com



# Model 1338 Manual Bandsaw

Manufactured in the United States of America

## Standard Features:

Spring loaded Carbide Guides with Rollers  
Combination Reduction Gearbox and  
Ring & Pinion Blade Drive  
Baldor® Motor  
3 HP Motor 3 Phase TEFC  
2 HP Single Phase ODP  
Infinitely Variable Blade Speeds  
Rite-Tension® Blade Tensioning Device  
Flood Type Wet Cutting System  
Powered Blade Brush  
110 Volts at Controls  
Overload and Undervoltage Protection  
Precision Ground Bed and Vise Jaws  
Quick Acting Vise  
Adjustable Stock Stop/Back-gauge  
Auto Shut-Off at End of Cut  
OSHA Blade Guarding  
Tiger-Tooth® Bi-Metal Blade  
Coolant for Initial Start-Up

## Specifications:

|                    |   |
|--------------------|---|
| Capacity           | Round 13"<br>Rectangular 13" x 38"<br>45° Angle 12" x 21" |
| Blade Size         | 1" x .035" x 15'- 6" (186")                               |
| Blade Speeds       | Infinitely Variable<br>70 - 375 SFPM                      |
| Blade Guides       | Carbide Guides with Rollers                               |
| Blade Tension      | Manual Rite-Tension®                                      |
| Electrical Options | 115-208-230/60/1<br>208-230-460/60/3                      |
| Coolant System     | Tank Capacity 8 gallons<br>Submersible Pump / 3 gpm       |
| Vise Control       | Quick Acting / Manual Screw<br>To 45°                     |
| Swivel Vise        |   |
| Feed Control       | Variable Hydraulic<br>w/ Counterbalance Spring            |
| Band Wheels        | 15" Diameter Cast Iron                                    |
| Bed Height         | 29"   |
| Floor Area         | 40"W x 102"L  |
| Shipping Weight    | 1,200 lbs.  |

## Factory Installed Options Available

Flush Hose w/ 8.5 gpm pump  
Powered Frame Raise and/or Powered Vise  
Laser Line Pointer  
Casters (Set of 4, 2 Locking)  
NFPA Electrics (w/disconnect)  
Work Light w/ transformer  
Stock Stand, 18"  
5' and 10' Non-Powered Roller Conveyor

## Other Models in the 1338 Family

Model 1318 13" x 18" Capacity Manual Saw  
Model 1316S Swivel Head 60° Miter Saw  
All models available w/ PLC controlled Semi-Automatic  
Operation

Please Contact Factory For Additional Options

*Specifications Subject to Change Without Notice*



2829 N. Burdick St.  
Kalamazoo, MI 49004  
Phone 269-345-1132  
Fax 269-345-0095  
Email [info@wellsaw.com](mailto:info@wellsaw.com)