

Wellsaw[®]
M A D E I N U . S . A .


MODEL 57
Manual Bandsaw



**WELLSAWS work harder and last longer
because they are built better.**

Wellsaw[®]
M A D E I N U . S . A .

2829 N. Burdick St.
Kalamazoo MI 49004
Phone: 269-345-1132
Fax: 269-345-0095
www.wellsaw.com



Packaging - Processing
Bid on Equipment
1-847-683-7720
www.bid-on-equipment.com

Model 57 Bandsaw

Manufactured in the United States of America

The **Wellsaw Model 57** offers accuracy, portability, and versatility. It can be quickly converted from horizontal to vertical operation. Lightweight yet very rugged.

Standard Features Include:

- CRigid Welded Steel Frame & Bed
- CAdjustable Spring-tension controlled Down-feed
- CConvertible (Horizontal/ Vertical)
- CMobile. Includes Wheel/ Handle Assembly
- CWork Table for Vertical operation
- CSix ball bearing Blade Guides
- CBaldor® Motor
- CThree Band Speeds
- CSafety Switch and Overload Protection
- CPrecision Ground Bed
- CReplaceable Pivot Bushings
- CAuto Shut-off at End of Cut
- COSHA Blade Guards
- CTiger Tooth® Blade

Options Available:

- CStock Stand
- CWet Coolant System
- CSpare Blade Package

Specification subject to change without notice.

The Original...Since 1926

Wellsaw
MADE IN U. S. A.



2829 N Burdick St.
Kalamazoo MI 49004
Phone: 269-345-1132
Fax: 269-345-0095
www.wellsaw.com

Specifications:

Capacity	
Round	5"
Flat	9"
Rectangular	5" x 7"
45E Angle	3-1/4" x 3-1/4"
Vertical Capacity	
Throat Depth	4-3/4"
Throat Height	8-3/4"
Work Table	4" x 6"
Blade Size	1/2" x .025 x 5'-4"(64")
Blade Speeds	54 - 100 - 190 SFPM
Blade Guides	Six Rollers on Cast Iron Supports
Blade Motor	1/2 HP Single Phase ODP
Vise Control	Manual Screw
Swivel Vise	To 45E
Band Wheels	8" Cast Iron
Bed Height	24"
Floor Area	21"W x 46"L
Shipping Weights	210 Lbs.

Packaging - Processing

Bid on Equipment

1-847-683-7720

www.bid-on-equipment.com